



StockView™


Pressure Sensor - Fuel / LoRa - Sigfox

The new SilentSoft platform allows to integrate the new **Neevo** Sensor. You can benefit from the StockView™ service in countries with LoRa and Sigfox networks (lora-alliance.org or sigfox.com).

The **Neevo** innovates allowing long range radio transmissions and reduces interference obstacles at installation (building, basement, buried tank etc...). The technology rests on Sigfox and LoRa networks and protocols.

Neevo is a Swiss product responding to high quality standards.


SilentSoft offers 3 references :



Standard

The pressure measured at the bottom of the tank is compared with the atmospheric pressure from close meteo sites.


LoRa:
Neevo-Lora -I-1S5-1EGF
Sigfox:
Neevo-SIGFOX -I-1S5-1EGF



Multi

One transmitter allows to manage two tanks in parallel. This option reduces costs when two tanks are physically side by side.

LoRa:
Neevo-Lora -I-2S-5/5-2EGF
Sigfox:
Neevo-SIGFOX -I-2S-5/5-2EGF



Differential

The pressure measured at the bottom of the tank is compared with the pressure from the second sensor installed in the tank on top of the measured product.

LoRa:
Neevo-Lora -I-2S-5/5-1DEGF
Sigfox:
Neevo-SIFOX-I-2S-5/5-1DEGF

Technical Data Sheet

Fuel tank



Neevo by SilentSoft

Sensor:

2 0-5V ratiometric inputs up to 2 SENS.5 pressure sensors

Data transmission:

LPWAN Sigfox or LoRa (869/915 MHz)

Supply:

Lithium Battery (3.0 V, 3.0 Ah)

Battery life:

5 to 10 years

IP protection level:

IP68 (with molding)

Dimensions / Weight:

91x69x31 mm / 120 gr

Temperature range:

-40°C to +60°C

Certifications:

 Ex ia [ia Ga] IIB T3
II 1(1) G

Certificate No.
SEV 19 ATEX 01 13 X
IECEX SEV 19.0009 X

For more information and advice about our solutions, please contact us or visit our web site, we are at your service!

